



High speed portable polisher for field assembly

POP-311



Features

Suitable for field assembly and/or re-polishing of optical connector in optical network installation and/or its maintenance.

Battery operated

Rechargeable nickel hydride battery (AA) or alkaline dry battery (AA) can be applied.

High speed polishing

80 sec for re-polishing of SC/FC connector

90 sec for polishing of MU-type connector

High quality

High polishing quality equivalent to that of factory use polisher can be achieved.

Light weight Portable polisher

Supplied in a handy-carrying case, in which other assembling tools can also be stored

Specifications

| Specifications | |
|------------------------------|---|
| Applicable connector/ferrule | SC-/FC-type connector plug, SC-/MU-type ferrule |
| Power supply | Rechargeable Ni-H battery or Alkaline dry battery (AA x 4) – Not Included AC power adapter (100V 50-60VA 50-60Hz) –Option |
| Dimensions | 90 w x 75 d x 212 h mm |
| Weight | 830 g (main body without batteries) |
| Standard set | Main body, Polishing jig for SC plug, Polishing plate(3) |
| Optional accessories | AC power adapter, Polishing jig for MU ferrule, Polishing jig for SC ferrule, Polishing jig for FC plug |
| Polishing performance | |
| Curvature radius | 10 – 25 mm |
| Apex offset | < 50 mm |
| Under cut | < 0.05 mm |
| Return loss | > 50 dB |



7034 Augusta Road Greenville SC 29605 P: 864-277-7200 F: 864-277-7290 www.fibersource.net